

~~RESTRICTED~~

ARMOR SECTION

WATERTOWN ARSENAL
WATERTOWN, MASS.

AD-A954 927

~~RESTRICTED~~
UNCLASSIFIED

Ex # 3a

①



WATERTOWN ARSENAL LABORATORY

MEMORANDUM REPORT

NO. WAL 710/713

Comparison of 24ST and 75ST Aluminum Alloys
on the Basis of Resistance to Perforation
by Fragment-Simulating Projectiles

DTIC FILE COPY

BY

J. F. SULLIVAN
Asst. Engineer

M. A. BROUGH
Proof Technician



This document has been approved
for public release and sale, its
distribution is unlimited.

DATE 8 January 1945

WATERTOWN ARSENAL
WATERTOWN, MASS.


UNCLASSIFIED

~~RESTRICTED~~

819 050

WAL 710/713
710/713

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

DTIC CLASS		X	
DTIC TAB			
Unannounced			
Justification			
Availability Codes			
By			
Distribution/			
Availability Codes			
Dist	Avail and/or Special		
A-1			

8 January 1945

Comparison of 24ST and 75ST Aluminum Alloys
on the Basis of Resistance to Perforation
by Fragment-Simulating Projectiles

3. Two test samples (one 12" x 12" and one 6" x 12"), free of perforations, were cut out of each sheet received from Aberdeen Proving Ground. These samples were clamped rigidly to wooden ballistic frames and the 12" x 12" samples were subjected to impact by cal. .45 steel-jacketed ball projectiles while the 6" x 12" pieces were tested with cal. .22 fragment-simulating projectiles, G-2, and with cal. .30 fragment-simulating projectiles, G-1-S. The results of these tests are shown in Table I.

1. O.O. 400.112/11981 - Wtn 400.112/3227 - 7 November 1944
2. WAL 762/247
3. WAL 762/253

UNCLASSIFIED

~~_____~~

4. Although the resistance of individual pieces of 24ST was sometimes higher than that of 75ST it is felt that the results disclose no significant difference between the resistance characteristics of the two alloys under impact of the projectiles employed in these tests. There is apparent, of course, the customary inferiority of these materials to Hadfield manganese steel of equivalent weight under these test conditions. It should be pointed out that this inferiority does not extrapolate to actual service conditions, because, under actual fragmentation tests (in which 20mm. high explosive shell are detonated) the subject materials appear to be superior to Hadfield manganese steel and it is considered that the latter tests are more significant of actual service conditions than any ballistic limit tests currently in use.

M. A. Brough

M. A. Brough
Proof Technician

J. F. Sullivan

J. F. Sullivan
Asst. Engineer

APPROVED:

E. L. Reed

E. L. Reed
Research Metallurgist
Acting Chief, Armor Section

RESTRICTED

TABLE I

Summary of Ballistic Tests Conducted at Watertown Arsenal
on Samples of 24ST and 75ST Duralumin Which Had Been
Previously Subjected to Fragmentation Tests
at Aberdeen Proving Ground

Type	Sample No.	Nominal Gauge	Actual Gauge	Grams/ Sq. Ft.	Equiv. Steel Gauge	Ballistic Limits		
						.45 ¹	G-22	G-1-S ³
75ST	8	.156	.154"	1016"	.055	922		
"	"	"	.154	1008	.054		960 [±] 25	1063 [±] 23
"	9	.156	.160	1043	.056	847		
"	"	"	.157	1028	.056		970 [±] 5	1074 [±] 27
"	2	.156	.156	1022	.055	887		
"	"	"	.155	1016	.055		955 [±] 10	1083 [±] 23
"	11	.125	.127	832	.046	772		
"	"	"	.123	798	.043		775 [±] 15	825 [±] 10
"	7	.125	.125	821	.044	753		
"	"	"	.125	816	.044		800 [±] 25	803 [±] 23
"	8	.125	.124	821	.044	790		
"	"	"	.127	838	.045		827 [±] 17	898 [±] 13
"	1	.102	.100	656	.035	522		
"	"	"	.101	664	.036		728 [±] 13	803 [±] 23
"	4	.102	.103	672	.036	537		
"	"	"	.102	674	.036		760 [±] 30	720 [±] 25
"	20	.102	.101	665	.036	541		
"	"	"	.101	662	.036		725 [±] 40	723 [±] 13
24ST	16-A-53	.156	.156	1031	.056	927		
"	"	"	.157	1028	.056		1030 [±] 10	1025 [±] 15
"	7-A-69	.156	.161	1046	.057	880		
"	"	"	.157	1022	.055		965	1042 [±] 17
"	13-A-67	.156	.157	1028	.056	929		
"	"	"	.158	1032	.056		983 [±] 23	1090 [±] 15
"	10-B-179	.125	.124	826	.045	720		
"	"	"	.123	834	.045		823 [±] 27	870 [±] 25
"	13-A-136	.125	.124	837	.045	777		
"	"	"	.128	836	.045		825 [±] 10	868 [±] 17
"	13-B-183	.125	.127	837	.045	736		
"	"	"	.126	836	.045		835 [±] 20	842 [±] 27
"	16	.102	.104	684	.037	568		
"	"	"	.105	678	.037		735 [±] 20	710 [±] 20
"	26	.102	.104	685	.037	539		
"	"	"	.104	672	.036		740 [±] 25	690 [±] 15
"	29	.102	.104	688	.037	522		
"	"	"	.104	682	.035		775 [±] 25	745 [±] 10
FOR COMPARISON:								
Hadfield Manganese Steel					.045	950	1675	1050

1. Cal..45 steel-jacketed ball projectile - 230 grains
2. Cal..22 fragment-simulating projectile - 17 grains
3. Cal..30 fragment-simulating projectile - 34 grains